DAD 260/10 EN1

Montagehinweis / *instruction for installation*

Bestehend aus einer zusammen verschraubten Untereinheit und Gehäuse, muss der Lautsprecher aufgeklappt über die Untereinheit an die vorgesehene Montagestelle mit 2oder4 Schrauben befestigt werden. Bei Kabelunterputz-Verlegung muss die Kabelleitung von hinten über die Untereinheit in den Lautsprecher eingeführt werden. Bei Kabelaufputz-Verlegung wird die Kabelleitung durch die seitliche Gummidurchführung durchgeführt.
Die Kabelleitung wird an die WAGO-Kunststoffklemme angeschlossen. Das aufgeklappte Gehäuse wir nun über den einzigartigen Klappmechanismus über die Untereinheit geklappt und via 2 Schrauben verschraubt. Zum Ende der Montage bitte alle vier Gehäuseschrauben auf festen Sitz überprüfen.

By novel mounting mechanism as a hinged junction box, the loudspeaker is attached by two screws to the sub-unit of the junction box at the intended mounting location. The cable line is led inside through the rubber bushings. The cable line is connected to the WAGO-plastic clamp. The upper unit of the connection box including the speaker housing is now folded onto the lower unit and screwed in place with two screws. At the end of the assembly, please check all four housing screws for tightness.