WAL-M 165/6 EN1

Montagehinweis / *instruction for installation*

Bestehend aus einer zusammen verschraubten Untereinheit und Gehäuse, muss der Lautsprecher aufgeklappt über die Untereinheit an die vorgesehene Montagestelle mit 2oder4 Schrauben befestigt werden. Bei Kabelunterputz-Verlegung muss die Kabelleitung von hinten über die Untereinheit in den Lautsprecher eingeführt werden. Bei Kabelaufputz-Verlegung wird die Kabelleitung durch die seitliche Gummidurchführung durchgeführt.
Die Kabelleitung wird an die WAGO-Kunststoffklemme angeschlossen. Das aufgeklappte Gehäuse wir nun über den einzigartigen Klappmechanismus über die Untereinheit geklappt und via 2 Schrauben verschraubt. Zum Ende der Montage bitte alle vier Gehäuseschrauben auf festen Sitz überprüfen.

Consisting of a sub-unit and housing screwed together, the loudspeaker must be opened up and fastened to the intended mounting location via the sub-unit using 2 or 4 screws. In the case of flush-mounted cables, the cable must be fed into the loudspeaker from behind via the subunit. In the case of surface-mounting, the cable is fed through the rubber grommet on the side. The cable line is connected to the WAGO-plastic clamp. The opened housing is now folded over the sub-unit using the unique folding mechanism and screwed in place via 2 screws. At the end of the assembly, please check all four housing screws for tightness.